



PRODUCT PROFILE 050 PVA SEALER POLY VINYL ACETATE

1950 Dr. Martin Luther King Jr. Pkwy. - Chico, Ca 95928 - (530) 345-9595 - Fax (530) 345-3589

DESCRIPTION:

050 PVA wall sealer (Poly Vinyl Acetate) is a high vehicle solid, low pigment volume vinyl wall sealer. Recommended for use as a sealer for all interior drywall and concrete surfaces which are to be painted with enamels and/or flat wall paints.

PHYSICAL PROPERTIES	
COLOR	WHITE
FINISH	FLAT
SOLVENT	WATER
DRY TO TOUCH	2-3 HOURS
% SOLIDS BY VOLUME	23%
% SOLIDS BY WEIGHT	36%
COVERAGE	150-300 SQUARE FEET
VISCOSITY	90-95 KREB UNITS
RECOAT TIME	6-12 HOURS

V.O.C.: LESS THAN 100 GRAMS PER LITER

ADVANTAGES:

- * Maximum sealing characteristics
- * Good hiding qualities
- * Meets clean air standards
- * Water thinned
- * Fast Drying
- * Easy application

**Refer to label for cautions and warnings



PRODUCT PROFILE 050 PVA SEALER POLY VINYL ACETATE

1950 Dr. Martin Luther King Jr. Pkwy. - Chico, Ca 95928 - (530) 345-9595 - Fax (530) 345-3589

TYPE OF PRODUCT:

A high vehicle solid, low pigment volume vinyl wall sealer. Produces maximum sealing and minimum of hide characteristics.

TYPICAL USES:

A sealer for interior drywall and concrete surfaces to be used under enamels and flat wall paint.

SURFACE PREPARATION:

Be sure all surfaces are dry, free from dirt, grease, wax, chalky paint, rust, efflorescence and stains. Dull or etch glossy, glazed or dense surfaces. Neutralize alkali conditions, remove and kill all mildew or any other contamination that would adversely affect the performance of this coating.

APPLICATION:

May be applied by brush, roller or airless spray equipment. Do not apply in temperature below 50°F.

DRYING TIME:

2-4 hours under normal conditions. Damp and cool weather could extend drying time.

NEW SURFACES:

Apply one uniform coat to seal new drywall.

COVERAGE:

150-300 square feet per gallon, depending on surface and application methods.

NOTE: PVA is a sealer, not a finish. A uniform coat is recommended.

THINNING AND CLEAN-UP:

Formulated ready for use. If thinning is necessary use small amount of water. Do not over thin. Clean brushes and equipment with water immediately after use.

COLORS:

White

PACKAGE SIZES: 5 gallon, 1 gallon

APPROX. WEIGHT PER GAL: 10.4 LB.