



PRODUCT PROFILE
330 INTERIOR SEMI-GLOSS LATEX
100% ACRYLIC

1950 Dr. Martin Luther King Jr. Pkwy. - Chico, Ca 95928 - (530) 345-9595 - Fax (530) 345-3589

DESCRIPTION:

330 semi-gloss interior latex enamel is a fast drying 100% acrylic finish for all kinds of primed or pre-painted interior surfaces. 330 is recommended where a semi-gloss finish is appropriate and for all living areas where durability and washability is desired.

PHYSICAL PROPERTIES	
COLOR	WHITE, 5 STOCK COLORS AND BASES
FINISH	SEMI-GLOSS
SOLVENT	WATER
DRY TO TOUCH	2-4 HOURS
% SOLIDS BY VOLUME	37%
% SOLIDS BY WEIGHT	47%
COVERAGE	300-400 SQUARE FEET
VISCOSITY	88-93 KREB UNITS
RECOAT TIME	6-12 HOURS

V.O.C.: LESS THAN 150 GRAMS PER LITER

ADVANTAGES:

- * Fast drying
- * Flexible strength
- * Meets clean air standards
- * Excellent washability
- * Water thinned
- * Extremely durable
- * Beautiful semi-gloss
- * Outstanding adhesion

**Refer to label for cautions and warnings



PRODUCT PROFILE

330 INTERIOR SEMI-GLOSS LATEX

100% ACRYLIC

1950 Dr. Martin Luther King Jr. Pkwy. - Chico, Ca 95928 - (530) 345-9595 - Fax (530) 345-3589

TYPE OF PRODUCT:

A premium quality semi-gloss latex enamel, designed for new or previously painted interior surfaces where a semi-gloss finish is desired.

TYPICAL USES:

Recommended for kitchens, bathrooms, doors and other interior surfaces where a medium sheen and durable finish is desired.

SURFACE PREPARATION:

Be sure all surfaces are dry, free from dirt, grease, wax, chalky paint, rust, efflorescence and stains. Dull or etch glossy, glazed or dense surfaces. Neutralize alkali conditions, remove and kill all mildew or any other contamination that would adversely affect the performance of this coating.

APPLICATION:

May be applied by brush, roller or airless spray equipment. If brushing, a good quality nylon brush is recommended. Do not apply when material, air and/or surface temperature below 50°F.

DRYING TIME:

Dries to touch in 2 hours. A second coat may be applied in 6-12 hours, depending on temperature.

PREVIOUSLY PAINTED SURFACES:

Fill or patch holes, spot prime bare or patched areas, or prime entire surface. Dull or etch glossy surfaces by sanding or any other suitable method.

NEW SURFACES:

Prime with suitable Corlin Paint primer. Apply one or more finish coats as required.

COVERAGE:

Approx. 350 square feet per gallon, depending on texture porosity of the surface to be painted.

THINNING AND CLEAN-UP:

Formulated ready for use. If thinning is necessary use small amount of water. Do not over thin. Clean brushes and equipment with water immediately after use.

COLORS:

White, Antique, Apache, Bone, Frost, Hurst Acoustic and Tint bases.

PACKAGE SIZES: 5 gallon, 1 gallon, quarts

APPROX. WEIGHT PER GAL: 10.4 LB.