



**PRODUCT PROFILE**  
**365 E.H.B. FLAT LATEX**  
**EXTRA HEAVY BODIED**

1950 Dr. Martin Luther King Jr. Pkwy. - Chico, Ca 95928 - (530) 345-9595 - Fax (530) 345-3589

**DESCRIPTION:**

365 E.H.B. Flat latex is an extra heavy bodied vinyl wall coating, formulated especially for the professional painter. Use on all interior drywall, plaster, wood or concrete walls and ceilings where a flat finish is desired.

<b>PHYSICAL PROPERTIES</b>	
COLOR	WHITE
FINISH	FLAT
SOLVENT	WATER
DRY TO TOUCH	1-2 HOURS
% SOLIDS BY VOLUME	34%
% SOLIDS BY WEIGHT	54%
COVERAGE	350-400 SQUARE FEET
VISCOSITY	108-113 KREB UNITS
RECOAT TIME	2-4 HOURS

**V.O.C.: LESS THAN 100 GRAMS PER LITER**

**ADVANTAGES:**

- \* Fast drying
- \* Excellent hiding
- \* Meets clean air standards
- \* Superb touch-up
- \* Water thinned
- \* Extremely durable
- \* Easy application
- \* Outstanding adhesion

\*\*Refer to label for cautions and warnings



## **PRODUCT PROFILE**

### **365 E.H.B. FLAT LATEX**

### **EXTRA HEAVY BODIED**

1950 Dr. Martin Luther King Jr. Pkwy. - Chico, Ca 95928 - (530) 345-9595 - Fax (530) 345-3589

#### **TYPE OF PRODUCT:**

An extra heavy bodied vinyl wall coating, formulated especially for the professional painter.

#### **TYPICAL USES:**

All interior drywall, plaster, concrete or hardboard surfaces where a flat finish is desired.

#### **SURFACE PREPARATION:**

Be sure all surfaces are dry, free from dirt, grease, wax, chalky paint, rust, efflorescence and stains. Dull or etch glossy, glazed or dense surfaces. Neutralize alkali conditions, remove and kill all mildew or any other contamination that would adversely affect the performance of this coating.

#### **APPLICATION:**

May be applied by brush, roller or airless spray equipment. Do not apply in temperature below 50°F.

#### **DRYING TIME:**

1-2 hours under normal conditions, a second coat may be applied in 2-4 hours depending on conditions. More time is required during cool, damp weather.

#### **PREVIOUSLY PAINTED SURFACES:**

Fill or patch holes, spot prime bare or patched areas, or prime entire surface. Apply one or more coats as required.

#### **NEW SURFACES:**

Apply one or more coats as required.

#### **COVERAGE:**

Approx. 350-400 square feet per gallon, depending on texture porosity of the surface to be painted.

#### **THINNING AND CLEAN-UP:**

This product is an extra heavy bodied latex paint and can be reduced with 1 to 2 gallons of water per 5 gallons of paint. Clean brushes and equipment with water immediately after use.

#### **COLORS:**

White

**PACKAGE SIZES:** 5 gallon, 1 gallon

**APPROX. WEIGHT PER GAL:** 12.1 LB.